

Technical Specifications

**All inclusive SAN-workspace-in-a-box.
The perfect entry-level solution for media.**



Server Chassis	4U server enclosure with rack mount kit, dual FRU power supplies / fan assemblies, and 6Gbit SAS drive backplane
Metadata Chassis	Embedded
UPS + PDU	not applicable
RAID Specs	2 x RAID 6 plus 1 x RAID 1; features the Aurora RAID 6 engine technology in a single controller configuration with 16GB of RAM (upgradeable to 128GB)
Drive Support	36 x 3.5-inch SAS 6Gbit/s hot-swap hard drives (incl. 2 spares), mirrored OS

Workspaces	1 embedded workspace
Operating System	Linux
Supported Client OS	Windows, MAC OSX, Linux
Supported File Systems	StorNext 4.2, HyperFS
Connectivity	FibreChannel: 4x8Gbit (expandable to 8x8 Gbit), Ethernet: 2x1Gbit
Scalability	No (but hardware can be utilized in a BrightDrive environment)
Number of Streams	3 streams (2K)
High Availability	No

Warranty	Yes, 12 months with advanced replacement; Warranty extension optional
Service Available	Full service and support

Electrical	Mechanical	Environmental
Voltage	Height 7" (178mm)	Operating Temp 10°-35°C (-40° +70°C non operational)
Current (Maximum)	Width 17.2" (437mm)	Rel. Humidity Maximum 90%
Power Supply	Depth 27.5" (699mm)	Certifications CE, FCC Class A
Power Consumption	Gross Weight 80 lbs (36.3 kg)	